

## TECHNICAL DETAILS

<b>WEIGHT/SQUARE</b> 242 lbs. 109.8 kg	<b>EXPOSURE</b> 5 <sup>5</sup> / <sub>8</sub> " 142.9 mm
<b>SHINGLES/SQUARE</b> 64 4 bundles/square	<b>GRANULE ADHESION</b> 0.45 g Typical Results
<b>WIDTH ± 1/8"</b> 13 <sup>1</sup> / <sub>4</sub> " 337 mm	<b>LENGTH ± 1/4"</b> 40" 1.02 m
<b>SQUARES/PALLET</b> 12	

## TEST COMPLIANCE

<b>ASTM</b> D7158 Class H	<b>ASTM</b> D3462
<b>ASTM</b> D3161 Class F	<b>ASTM</b> D3018 Type I
<b>ASTM</b> E108 Class A Fire Rating	<b>CSA</b> A123.5
<b>ICC APPROVAL</b> ESR-3150	<b>FBC APPROVAL</b> #14809
	
	
<b>CEC</b> Title 24, Part 6 Compliant <sup>§</sup>	

See page 2 for solar reflectance technical data.

## FEATURES & BENEFITS

- Scotchgard™ Protection from 3M
- Algae Resistant
- Superior Granular Embedment
- The Zone® Nailing Area
- Double Rain Seal Protection
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties

<sup>§</sup> ENERGY STAR, CRRC and California Energy Code Title 24, Part 6 only apply to Highlander® Dove White shingles.

## LAMINATED ARCHITECTURAL SHINGLES



## PRODUCT USE

The Highlander®, Highlander® AR and Highlander® featuring Scotchgard™ are laminated asphalt shingles used whenever increased flexibility, architectural design, tensile strength, and tear-resistance in shingles is desired. The Highlander® line features the exclusive nailing accuracy-enhancing design of The Zone®. The larger nailing area of The Zone® dramatically improves correct fastener placement. Highlander® Dove White shingles meet the required reflectance to be designated with some of the industry's leading energy conservation standards: ENERGY STAR, CRRC listing, and California Energy Code Title 24, Part 6 compliance. Please consult Malarkey's Technical Services Department for approval of roof systems.

## COMPOSITION & MATERIALS

The Highlander® shingle line is manufactured on a woven fiberglass mat and impregnated on both sides with bitumen (asphalt) that is compounded with a fire-retardant mineral stabilizer. The Highlander® line is surfaced with embedded ceramic granules for ultraviolet protection and weatherability. Highlander® AR and Highlander® featuring Scotchgard™ are surfaced with algae resistant granules.

## APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper, at [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM), or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

## PRECAUTION

For best results, Malarkey recommends The Highlander® shingle line be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), additional deck protection is required. The Highlander® shingle line has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. In high wind areas and on slopes greater than 12" (305 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

## WARRANTY

Malarkey Roofing Products® offers various warranties to meet specific requirements. The warranty packages available for the Highlander® shingle line include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Highlander® AR features 10 years of algae resistant protection and Highlander® featuring Scotchgard™ carries a 20-year Scotchgard™ warranty against algae growth. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

The Highlander® shingle line and other Malarkey products are available throughout North America and Pacific Rim countries. Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) Inventory SKU numbers for this product: 271 Highlander®, 276 Highlander® AR and 277 Highlander® featuring the Scotchgard™ Algae Resistant Shingle Protector from 3M

### TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

### CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191  
Portland, OR 97217-7472 or 800.545.1191  
P.O. Box 17217 Fax: 503.289.7644  
Portland, OR 97217-0217

LAMINATED  
ARCHITECTURAL SHINGLES

## SOLAR REFLECTANCE TECHNICAL DATA

Highlander® Dove White is listed with the Cool Roof Rating Council.  
Highlander® Dove White has tested to these radiative property values:



Cool Roof Rating Council ratings are determined for a fixed set of conditions, and may not be appropriate for determining seasonal energy performance. The actual effect of solar reflectance and thermal emittance on building performance may vary.

Manufacturer of product stipulates that these ratings were determined in accordance with the applicable Cool Roof Rating Council procedures.

	INITIAL	WEATHERED
SOLAR REFLECTANCE	0.27	0.27
THERMAL EMITTANCE	0.90	0.96
SOLAR REFLECTIVE INDEX (SRI)	28	31
Related Product ID	0850-0014	
Licensed Manufacturer ID	0850	
Classification	Production Line	



Energy Star only applies to the Highlander® Dove White shingle.  
Energy Star is only recognized in the U.S., not in Canada.

## TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
technicalinquiries@malarkeyroofing.com

## CORPORATE OFFICE:

3131 N. Columbia Blvd.  
Portland, OR 97217-7472  
P.O. Box 17217  
Portland, OR 97217-0217

Telephone: 503.283.1191  
or 800.545.1191  
Fax: 503.289.7644